

e-Bridge App Requirements (iOS)

1. Minimum System Requirements

- a. iOS device (iPhone, iPad or iPod Touch) running iOS v9.0 or later (as of e-Bridge v12.0)
Note: iPod Touch not recommended. GD has observed issues receiving push notifications for new messages if iPod is left idle for an extended period of time.
- b. If any Mobile Device Management (MDM) software is used, access to microphone and camera must be allowed for sending voice, picture, video messages and/or live streaming video. iOS device must also be able to receive push notifications from Apple Push Notification service (APNs).
- c. If using the Location Tracking feature, iOS device MUST have a built-in GPS receiver. As of the time of this writing, all iPhones have GPS, but only iPads with Cellular Data capability have GPS. WiFi only iPads do NOT have GPS and therefore cannot be used for the Location Tracking feature of e-Bridge.

2. Network Requirements

The following ports need to be open in any firewalls between the iOS device and the internet for e-Bridge to communicate:

Port # (Protocol)	Direction	Destination
80 (TCP)	Outgoing	96.242.183.10 Note: This is for uploading log files to GD Tech Support for troubleshooting.
81 (TCP)	Outgoing	http://www.gdserver.net Note: This is for the Secure Messaging portion of the app.
443 (TCP)	Outgoing	https://messaging.gdserver.net Note: This is for the Secure Messaging portion of the app.
5223 (TCP)	Outgoing	17.0.0.0 Netmask 255.0.0.0 Note: CIDR Notation for above: 17.0.0.0/8 Note: This is the entire address block registered to Apple. This is used for receiving push notifications on iOS devices. See https://support.apple.com/en-us/HT203609 for more info.
5060, 5061 (UDP/TCP)	Both	66.227.100.0 Netmask 255.255.255.0 199.7.172.0 Netmask 255.255.255.0 199.7.173.0 Netmask 255.255.255.0 199.7.174.0 Netmask 255.255.255.0 199.7.175.0 Netmask 255.255.255.0 Note: CIDR Notation for above: 66.227.100.0/24, 199.7.172.0/22 Note: This is for the Live Streaming portion of the app.
20000-20099 (UDP)	Both	66.227.100.0 Netmask 255.255.255.0 199.7.172.0 Netmask 255.255.255.0 199.7.173.0 Netmask 255.255.255.0 199.7.174.0 Netmask 255.255.255.0 199.7.175.0 Netmask 255.255.255.0 Note: CIDR Notation for above: 66.227.100.0/24, 199.7.172.0/22 Note: This is for the Live Streaming portion of the app.

e-Bridge App Requirements (iOS)

For e-Bridge Live Streaming, only networks with a single Network Address Translation (NAT) layer are supported. If using Verizon Wireless hotspots they must be configured with a static, public IP address to eliminate a double NAT.